

MATERIAL SAFETY DATA SHEET
ABS 55Y-LV SOLVENT CEMENT

Page : 1

SLUYTER COMPANY LTD.

375 Steelcase Road East
Markham, Ontario L3R 1G3 Canada
Tel (905) 475-6011 Fax (905) 475-3119

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER-----SLUYTER COMPANY LTD.
375 Steelcase Road East
Markham, Ontario L3R 1G3
Canada
Tel (905) 475-6011
PRODUCT NAME-----ABS 55Y-LV (Solvent Cement).
PRODUCT USES-----For welding plastic pipes and fittings.
CHEMICAL FAMILY-----Acrylonitrile-Butadiene Styrene.

SECTION 02: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS / %	CAS / TLV	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
METHYL ETHYL KETONE 10 - 60	78-93-3 200 ppm	2737 mg/kg Oral (Rat)	23500 mg/m3 8 Hours Inhalation (Rat)
TOLUENE 10 - 50	108-88-3 200 ppm	>2 g/kg Skin (Rabbit)	8000 ppm 8 hours Inhalation (Rat)
ACETONE 10 - 20	67-64-1 750 ppm	9750 mg/kg Oral (Rat)	16000 ppm 4 hours Inhalation (Rat)

SECTION 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:-----
SKIN CONTACT-----Can cause moderate skin irritation,
defatting and dermatitis.
SKIN ABSORPTION-----Not applicable.
INHALATION-----As described below.
INHALATION CHRONIC-----Breathing of high vapour concentrations
could cause dizziness, headache or even
unconsciousness .May be anesthetic which
could result in other central nervous
system effects.
INGESTION-----Can cause gastro-intestinal irritation,
nausea, vomiting and diarrhea. Small
amounts of liquid aspirated into
respiratory system could cause severe
health effects (e.g. Bronchopneumonia or
Pulmonary Edema).
EYE CONTACT-----Contains materials that are severely
irritating to the eyes. If not removed
promptly, it will injure the eye tissue
and may cause permanent eye damage.
EFFECTS OF ACUTE EXPOSURE-----
EFFECTS OF CHRONIC EXPOSURE-----May cause damage to the central nervous
system. Prolonged or repeated skin contact
may cause drying or cracking of the skin.

Ref: 0000100E

Preparation Date : May.07.2015

EMERGENCY - CALL CANUTEC (613) 996-6666 (Collect)

MATERIAL SAFETY DATA SHEET
ABS 55Y-LV SOLVENT CEMENT

SECTION 04: FIRST AID MEASURES

EYE CONTACT-----Check for and remove any contact lenses. Immediately flush with water for a minimum of 20 minutes and get medical attention.

SKIN CONTACT-----Remove contaminated clothing. Wash affected area with water and soap. Seek medical attention if irritation occurs or persists.

INHALATION-----Remove patient to fresh air. If not breathing, trained personnel should administer artificial respiration. Get medical attention.

INGESTION-----Do NOT induce vomiting. Get immediate medical attention.

ADDITIONAL INFORMATION-----Contact your local poison control centre.

SECTION 05: FIRE FIGHTING MEASURES

FLAMMABILITY-----Flammable.

UNDER WHAT CONDITIONS-----Extremely flammable liquid. Dangerous fire hazard when exposed to heat, flame or temperatures above the flash point. As vapours are heavier than air, they may travel to a source of ignition and flash back.

SPECIAL PROCEDURES-----A self-contained breathing apparatus is required for fire fighting personnel. Use water spray to cool fire exposed surfaces and to protect personnel.

FLASH POINT (METHOD)----- -4°C TAG Closed Cup.

AUTO IGNITION TEMPERATURE-----480°C.

UPPER FLAMMABLE LIMIT (% VOL)-----11.50.

LOWER FLAMMABLE LIMIT (% VOL)-----1.80.

EXTINGUISHING MEDIA-----Alcohol foam, CO2 or dry chemical.

HAZARDOUS COMBUSTION PRODUCTS-----Traces of monomers. Oxides of Carbon (CO and CO2). Hydrogen Cyanide.

SENSITIVITY TO MECHANICAL-----Not available.

IMPACT

SENSITIVITY TO STATIC-----May be sensitive.

DISCHARGE

SECTION 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL-----Ventilate. Remove all sources of ignition, open flames, sparks and heaters. Wear protective gear (See SECTION 8). Small spills can be wiped. Large spills must be collected for disposal. Use a non-combustible absorbent inorganic material. Prevent run-off into drains, sewers and other waterways.

SECTION 07: HANDLING AND STORAGE

HANDLING PROCEDURES-----Avoid skin and eye contact. Avoid breathing vapours. Use adequate ventilation. Keep away

MATERIAL SAFETY DATA SHEET
ABS 55Y-LV SOLVENT CEMENT

Page : 3

from heat, sparks and open flame.
STORAGE NEEDS-----Store away from all sources of heat and ignition. Store in well ventilated area. Keep container closed and out of reach from children and pets when not in use.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:-----
EYE/TYPE-----Safety glasses.
RESPIRATORY/TYPE-----None required for normal use if adequate ventilation is maintained. Use NIOSH/MSHA approved respirator if the TLV is exceeded.
GLOVES/ TYPE-----Wear impervious gloves (Neoprene or Rubber).
CLOTHING/TYPE-----Not applicable.
FOOTWEAR/TYPE-----Not applicable.
OTHER/TYPE-----Eye bath and safety shower.
VENTILATION REQUIREMENTS-----Natural or mechanical (Explosion Proof) ventilation to keep vapour levels well below the TLV.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE-----Liquid.
ODOUR-----Aromatic Solvent odour.
SPECIFIC GRAVITY-----0.86 - 0.90.
ODOUR THRESHOLD (ppm)-----25 ppm.
VAPOUR PRESSURE-----22 mmHg @ 20°C.
VAPOUR DENSITY (AIR=1)----- >1.00.
EVAPORATION RATE-----1.80 (NBUAC = 1).
BOILING POINT (deg C)-----110°C.
pH-----Not applicable.
SOLUBILITY IN WATER (% W/W)-----Negligible.
COEFFICIENT OF WATER\OIL-----Not available.
DISTRIBUTION
FREEZING POINT----- <0°C.
MELTING POINT (deg C)-----Not applicable.
MOLECULAR WEIGHT-----Not applicable.

SECTION 10: STABILITY AND REACTIVITY

INCOMPATIBILITY-----Strong acids and strong bases. Chlorinated solvents. Oxidizing agents.
REACTIVITY CONDITIONS-----Excessive heat, sparks and open flame.
HAZARDOUS PRODUCTS OF DECOMPOSITION-----Styrene and Acrylonitrile monomer. Oxides of Carbon (CO and CO2). Toxic fumes. Smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMIT OF MATERIAL-----See "HAZARDOUS INGREDIENTS" in SECTION 2.
IRRITANCY OF MATERIAL-----Moderate.
SENSITIZING CAPABILITY OF MATERIAL-----Not available.
CARCINOGENICITY OF MATERIAL-----Reversible liver damage at high dosages is possible. Residual amounts of Acrylonitrile and Styrene monomer may be present in decomposition but not in normal use. These are both suspected carcinogens.

Ref: 0000100E

Preparation Date : May.07.2015

EMERGENCY - CALL CANUTEC (613) 996-6666 (Collect)

