

MATERIAL SAFETY DATA SHEET
SILICONE C-20

Page : 1

SLUYTER COMPANY LTD.

375 Steelcase Road East
Markham, Ontario L3R 1G3 Canada
Tel (905) 475-6011 Fax (905) 475-3119

SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER-----SLUYTER COMPANY LTD.
375 Steelcase Road East
Markham, Ontario L3R 1G3
Canada
Tel (905) 475-6011
PRODUCT NAME-----SILICONE C-20.
CHEMICAL FAMILY-----Silicone Solvent Blend.
PRODUCT USES-----Silicone lubricant and release agent.

SECTION 02: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS / %	CAS / TLV	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
PETROLEUM DISTILLATES			
60 - 90	64741-65-7 Not Available	> 8000 mg/kg Oral (Rat)	>5900 mg/kg 4 Hours Inhalation (Rat)

SECTION 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:-----
SKIN CONTACT-----Can cause moderate skin irritation,
defatting and dermatitis.
SKIN ABSORPTION-----Not applicable.
INHALATION-----See "EFFECTS OF CHRONIC EXPOSURE", below.
INHALATION CHRONIC-----Can cause inflammation of the respiratory
system. Breathing of high vapour
concentrations could cause dizziness,
headache or even unconsciousness.
INGESTION-----Aspiration of liquid into lungs can cause
chemical pneumonitis.
EYE CONTACT-----Severe irritation, redness, watering and
blurred vision.
EFFECTS OF ACUTE EXPOSURE-----Refer to "ROUTE ENTRY" section.
EFFECTS OF CHRONIC EXPOSURE-----May cause damage to the central nervous
system. May cause nausea, headache,
dizziness and drowsiness.

SECTION 04: FIRST AID MEASURES

EYE CONTACT-----Check for and remove any contact lenses.
Immediately flush with water for a minimum
of 20 minutes and get medical attention.
SKIN CONTACT-----Remove contaminated clothing. Wash
affected area with water and soap. Seek
medical attention if irritation occurs or persists.
INHALATION-----Remove patient to fresh air. If not
breathing, trained personnel should
administer artificial respiration. Get
medical attention.
INGESTION-----Get immediate medical attention.
ADDITIONAL INFORMATION-----Contact your local poison control centre.

MATERIAL SAFETY DATA SHEET
SILICONE C-20

Page : 2

SECTION 05: FIRE FIGHTING MEASURES

FLAMMABILITY-----Flammable.
UNDER WHAT CONDITIONS-----Combustible product. May ignite if exposed to sources of heat, sparks, open flames or temperatures above the flash point.
SPECIAL PROCEDURES-----A self-contained breathing apparatus is required for fire fighting personnel. Use water spray to cool fire exposed surfaces and to protect personnel.
FLASH POINT (METHOD)-----50°C TAG Closed Cup (Concentrate).
AUTO IGNITION TEMPERATURE-----227°C.
UPPER FLAMMABLE LIMIT (% VOL)-----6.10.
LOWER FLAMMABLE LIMIT (% VOL)-----1.00.
EXTINGUISHING MEDIA-----Alcohol foam, CO2 or dry chemical.
HAZARDOUS COMBUSTION PRODUCTS-----Oxides of Carbon (CO and CO2). OXIDES OF SILICON.
SENSITIVITY TO MECHANICAL-----Yes.
IMPACT
SENSITIVITY TO STATIC-----May be sensitive.
DISCHARGE

SECTION 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL-----Ventilate. Remove all sources of ignition, open flames, sparks and heaters. Wear protective gear (See SECTION 8). Small spills can be wiped. Large spills must be collected for disposal. Use a non-combustible absorbent inorganic material. Prevent run-off into drains, sewers and other waterways. CAUTION: Surfaces may be slippery after use, clean thoroughly with a mineral spirits based cleaner.

SECTION 07: HANDLING AND STORAGE

HANDLING PROCEDURES-----Avoid skin and eye contact. Avoid breathing vapours. Use adequate ventilation. Keep away from heat, sparks and open flame.
STORAGE NEEDS-----Store in a cool area, away from all sources of heat and ignition. Store in a dry, well ventilated area. Do NOT store above 49°C.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:-----
EYE/TYPE-----Safety glasses.
RESPIRATORY/TYPE-----If used indoors on a continuous basis or if the TLV is exceeded, the use of a cartridge type respirator (NIOSH/MSHA approved) is recommended.
GLOVES/ TYPE-----Wear impervious gloves (Neoprene or Rubber).
CLOTHING/TYPE-----Not applicable.
FOOTWEAR/TYPE-----Not applicable.
OTHER/TYPE-----Eye bath and safety shower.
VENTILATION REQUIREMENTS-----Natural or mechanical (Explosion Proof) ventilation to keep vapour levels well below the TLV.

MATERIAL SAFETY DATA SHEET
SILICONE C-20

Page : 3

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE-----Liquid.
ODOUR-----Little or no odour.
SPECIFIC GRAVITY-----0.79 - 0.82.
ODOUR THRESHOLD (ppm)-----Not available.
VAPOUR PRESSURE----- < 10 mmHg @ 38°C.
VAPOUR DENSITY (AIR=1)-----4.50.
EVAPORATION RATE----- > 1.00 (NBUAC = 1).
BOILING POINT (deg C)-----150°C - 200°C.
pH-----Not applicable.
SOLUBILITY IN WATER (% W/W)-----Not soluble.
COEFFICIENT OF WATER/OIL-----Not available.
DISTRIBUTION
FREEZING POINT----- < 0°C.
MELTING POINT (deg C)-----Not applicable.
MOLECULAR WEIGHT-----Not applicable.

SECTION 10: STABILITY AND REACTIVITY

INCOMPATIBILITY-----Strong acids and strong bases. Oxidizing agents.
REACTIVITY CONDITIONS-----Excessive heat, sparks and open flame.
HAZARDOUS PRODUCTS OF-----Oxides of Carbon (CO and CO2). Toxic
DECOMPOSITION fumes. Smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMIT OF MATERIAL-----See "HAZARDOUS INGREDIENTS" in SECTION 2.
IRRITANCY OF MATERIAL-----Irritant upon prolonged exposure.
SENSITIZING CAPABILITY OF-----Not available.
MATERIAL
CARCINOGENICITY OF MATERIAL-----No information is available and no adverse
carcinogenic effects are anticipated.
TERATOGENICITY-----No information is available and no adverse
teratogenicity effects are anticipated.
MUTAGENICITY-----No information is available and no adverse
mutagenicity effects are anticipated.
REPRODUCTIVE EFFECTS-----No information is available and no adverse
reproductive effects are anticipated.
SYNERGISTIC MATERIALS-----Not available.

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL-----Not available. Can be dangerous if allowed
to enter drinking water intakes. Product
has an unaesthetic appearance and can be a
nuisance. Do not contaminate domestic or
irrigation water supplies, lakes, streams,
ponds and rivers.
BIODEGRADABILITY-----Not available. The solvent portion of this
product is biodegradable and vaporizes rapidly.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL-----Spilled material and water rinses are
classified as chemical waste. To be
disposed of in accordance with current
Local, Provincial and Federal regulations.

MATERIAL SAFETY DATA SHEET
SILICONE C-20

Page : 4

SECTION 14: TRANSPORT INFORMATION

T.D.G. CLASSIFICATION-----

- (1)----- (1j) In containers up to 1 litre -
shipped as CONSUMER COMMODITY. If the
shipment exceeds 500 kg in weight, shipped
as CONSUMER COMMODITY - PETROLEUM
DISTILLATES N.O.S. (MINERAL SPIRITS) CLASS
3.
- (2)----- (2j) In containers over 1 litre -
PETROLEUM DISTILLATES N.O.S. (MINERAL
SPIRITS) CLASS 3 UN1268 P.G. II.

SECTION 15: REGULATORY INFORMATION

CPR COMPLIANCE-----This product has been classified in
accordance with the hazard criteria of the
CPR and the MSDS contains all the
information required by the CPR.

WHMIS CLASSIFICATION-----Class B Div.3.

SECTION 16: OTHER INFORMATION

IMPORTANT:-----The information on this Material Safety
Data Sheet is furnished without warranty,
expressed or implied. All the information
appearing herein is based upon data
obtained from manufacturers and/or
recognized technical sources. While the
information is believed to be accurate, we
make no representations for the accuracy
or sufficiency.